



# MEDISEND®super/C

Pulsating magnetic field and Bioresonance

The **MEDISEND®super** and the **MEDISEND®super C** are two of the most popular magnetic field devices developed by Dr. W. Ludwig used in practices and clinics.



**First of all:**

The devices **MEDISEND®super** and **MEDISEND®super C** differ in only one feature: The **MEDISEND®super C** has an interface to connect a computer with the **AMScomsystem**. Thus it is possible to use **digitized remedies** for application. You will read more about the **AMScomsystem** on the back of this brochure. Apart from that interface they are identical devices with the same functions and settings. An upgrade with the interface for a **MEDISEND®super** is **not** possible.

**The MEDISEND®super devices combine proven methods of natural and experiential medicine:**

- Pulsating magnetic field
- Bioresonance methods

## MEDISEND®super and MEDISEND®super C...

are developed by Dr. rer. nat. W. Ludwig®, Institute for Bioinformative Medicine, Weikersheim. You use the **pulsating electromagnetic field** as an **application signal** and additionally as a **carrier wave for exogenous and endogenous bioinformation/substrates**. Together with numerous of users Dr. Ludwig found specific frequency programs for a multitude of applications to stimulate the self-healing capacities.

have each one **frequency generator** with the frequency bandwidth of 0.1 - 1000 Hz. Both devices offer further possibilities for more frequency modulation.

use the **MAGNETO-loop** as an applicator for applying the magnetic field. The loop is uncomplicated in handling and more handy than for example a large mat.

prevent electrosmog and its transmission through the **built-in rechargeable battery**. This is decisive for electrosensitive people and for the transfer of endogenous and exogenous bioinformation.

give the possibility to connect a **MEDICUP** as well as **hand electrodes**. These allow you to transfer **analog information to the magnetic field** – such as **exogenous** (e.g. homeopathic remedies) and **endogenous** (body-specific) information.

The **MEDISEND®super C** includes a **digital interface** to be connected to a laptop with the software **AMScomsystem** to work with **digitalized bioinformation** (BIOWAVEs). This allows you to use the digital information for transmission, testing and application as well as transferring and storing it onto the small **METRONOM C** device.

pulsating electromagnetic field for application and information transfer →

Frequency spectrum 0.1 - 1000 Hz →

handy applicator →

built-in battery →

analog und digital substrate transfer ↗

# MEDISEND®super/C

## Improving the ability of regulation

Usage →

The handling of the **MEDISEND®super devices** is very simple: Use the rotary knob to set the **desired frequency**, which you can either test with a **suitable test method** or take from the delivered **list which is based on experiences** from different therapists. Then you start the device. The connected **MAGNETO-loop** emits the pulsating magnetic field at the selected frequency. Place the loop on or close to the body to transmit the pulsating magnetic field. The **physiological range** reaches up to **2 m / 6.6 feet** in diameter.

Bio-  
resonance →

The devices are very suitable for transferring **exogenous** (e.g., homoeopathic remedies) and **endogenous** (body's own) bioinformation with the pulsating magnetic field and thus to use them during the application.

The power supply is provided by a **rechargeable battery**. With a switch you disconnect the device from the power supply. That ensures that **no additional electrosmog** is generated and transmitted during the application.

An application usually takes **15 minutes**, longer or shorter duration is also possible.

You can use the pulsating magnetic field as a **stand-alone application** or **combine other regulative methods** with it. For example, you can do reflexology during the application of the magnetic field or use the time for the duration of an acupuncture session.

Frequencies

Before and after the application drinking **plenty of clear water** will help drainage and cleansing.

→

The **MEDISEND®super devices** each have one **frequency generator**. The frequencies are set using a rotary knob. You can set the frequencies in the range of 0.1 up to 1000 Hz. The **harmonics** emitted by the **MEDISEND®super devices** reach up to the **MHz range**. Thus the devices generate all **RIFE and CLARK frequencies** up to 10 MHz.

Furthermore, you have the choice between **two frequency sweeps/scans**: 1000 to 1 Hz and 100 to 1 Hz. In these cases, the device runs through all frequencies within the selected bandwidth within approx. eight seconds. The frequency sweep starts at 1000 or 100 Hz, passes through all frequencies down to 1 Hz and then starts again from the beginning. Thus the body is offered a wide range of frequencies to **stimulate the regulation**. The frequency scans are often chosen to **support detox procedures** or to **start a series of applications**.

selection  
of  
frequencies →

You can use the provided **list that shows you a lot of experience data** to select frequencies. For complex questions, it is useful if you support the selection of the frequencies by a **test procedure**, such as testing with a tensor, kinesiology, EAV or RAC.

The AMS regularly offers a **tensor seminar** once or twice a year where you can learn how to use the tensor. The seminar takes place in the South of Germany and is held in German language. Dates and more information can be found on our website [www.magnetotherapy.de](http://www.magnetotherapy.de) in the menu item **Seminars**.

In addition to the different adjustable frequencies (among others it is always possible to set **7.8 Hz, the main value of the Schumann frequency spectrum**), the **Geomagnetic frequencies** and the **Solar frequencies** are always also generated by the **MEDISEND®super devices** - **regardless** of the frequency you choose for the application.

Environmental  
signals →

Schumann, Geomagnetic and Solar frequencies are our natural **environmental signals**. The exact description for these signals can be found on our double-paged information sheet **Magnetic field therapy - Bioresonance - Bioinformative Methods** or on our website [www.magnetotherapy.de](http://www.magnetotherapy.de) in the menu item **Basics of the magnetic field therapy**.

## Transfer of bioinformation - analogue and digital

There are **suitable accessories** for the **MEDISEND®super devices**, some of which are included in the scope of delivery. You can also purchase some other accessories **optionally**.

### → **MAGNETO-loop** for transmitting the pulsating magnetic field (included in the scope of delivery):

In order to be able to apply the electromagnetic field, an applicator has to be connected to the device, e.g. the **MAGNETO-loop**. The electromagnetic field comes out of the MAGNETO-loop. For the application, it is placed **on or close to the body**.

The **physiological effective range** of the electromagnetic field emitted by the loop is up to 2 m / 6.6 feet in diameter. It is **neither visible nor audible**. Very sensitive people sometimes feel something - but that does not have to be.

A pulsating electromagnetic field has the ability to **transport and transmit information**. This is comparable to the radio waves coming from the television or the radio: Here, a transmission of picture and sound is transferred by a modulated carrier wave (e.g. FM frequencies). Within the sense of bioresonance according to Dr. W. Ludwig, the pulsating electromagnetic field is additionally used as a **carrier wave** for bioinformation. It is called transfer of **exogenous** (foreign to the body) or **endogenous** (body's own) bioinformation.

In order to use the magnetic field as a **carrier wave for bioresonance**, it is possible to connect a MEDICUP and the hand electrodes to the device.

### → **MEDICUP** for the transmission of exogenous information (optionally available):

To transfer exogenous information, place the medication (e.g. any homeopathic remedy) into the connected **MEDICUP**. As soon as you have started the application with the device, the electromagnetic field acts not only as an **application signal**, but also as a **carrier wave** for the information that is inside the MEDICUP. The transmission of information is **independent** of the frequency you choose: **Any frequency** is a carrier wave and can be used for **transmitting bioinformation**.

As with the selection of the frequency, it is also advisable to use a **suitable testing method** to choose the substrates that you want to transfer.

### → **Hand electrodes** for the transmission of endogenous information (optionally available):

**Endogenous (body's own) information** can also be transmitted with the pulsating electromagnetic field by connecting hand electrodes to the device. Via the **symmetrical skin contact** (right and left half of the body), the endogenous bioinformation is tapped/scanned by the hand electrodes and returned to the body in the form of „**attention signals**“ in the sense of bioresonance.

The hand electrodes are used to **receive** the information of the complete body biofield. This received information is modulated onto the magnetic field emitted by the MAGNETO-loop and thus **returned to the body**.

The application of the pulsating electromagnetic field in **combination with endogenous and exogenous information** supports especially any **detox processes**.

The MAGNETO-loop emits the pulsating magnetic field



Transfer of information

MEDICUP for exogenous information



Hand electrodes for endogenous information



## Digital transfer with the AMScomsystem - The optimal supplement to the MEDISEND®super C



With the **MEDISEND®super C**, it is possible to use not only analog but also **digitized substrates for the exogenous transmission** of information. For this purpose we developed the software **AMScomsystem** and digitized over 6,000 substrates (homeopathic remedies, Bach flowers, nosodes, phytotherapeutics, etc.). These digitized information we call **BIOWAVES**, which we have put together in eight different packages. You control your **MEDISEND®super C** with the **computer** and transfer the selected BIOWAVES during the application using the magnetic field.

### Please note:

It is **not** possible to retrofit the **MEDISEND®super** later with an interface for the computer connection. If you want to leave the option of using the computer open for the future, but do not want to buy it immediately, you should invest in the **MEDISEND®super C** to start with.

## Combination with small devices

Two of our handy **small devices** can be combined particularly well with the **MEDISEND®super devices**

### CEPES-Laser®Vario:

It is connected to the **MEDISEND®super/C** with its cable and is used simultaneously with the application of the electromagnetic field. The red-light laser emits a pulsating magnetic field at the frequency set at the **MEDISEND®super/C**, as well as all exo- and endogenous bioinformation provided by the MEDICUP and hand electrodes.



### METRONOM C:

One of our practical small devices. It has five programs and provides a storage space where you can save a BIOWAVE digital information with the **MEDISEND®super C** in combination with the **AMScomsystem software**. During the usage of the **METRONOM C** device, the stored BIOWAVE can be patched in to each of the five programs. The information of the BIOWAVE is modulated on the emitted magnetic field and thus transferred by it. It is ideal for therapists as a loaner for patients.



# MEDISEND®super/C

### Technical Data:

<b>Magnetic field frequencies:</b>	Band width 0.1 - 1000 Hz / two frequency sweeps/scans: 1000 - 1 Hz and 100 - 1 Hz
<b>Physiological effective range:</b>	up to 2 m / 6.6 feet in diameter
<b>Battery:</b>	built-in rechargeable battery
<b>Weight:</b>	1.5 kg / 3.3 pounds without applicators
<b>Size:</b>	26.5 x 19.0 x 10.6 cm / 10.4 x 7.5 x 1.8 inches
<b>Scope of delivery:</b>	<b>MEDISEND®super</b> or <b>MEDISEND®super C</b> , applicator (MAGNETO-loop), battery charger, manual Only <b>MEDISEND®super C</b> : two connecting cables for laptop and METRONOM C
<b>Not part of the scope of delivery:</b>	MEDICUP, hand electrodes, METRONOM C, CEPES-Laser®Vario, Laptop and AMScomsystem software. You can purchase these items <b>optionally</b> .
<b>Warranty:</b>	2 years
<b>Accessories (optional):</b>	
<b>MEDICUP:</b>	bipolar cup (height 7 cm / 2.8 inches, diameter 5,5 cm / 2.2 inches), connecting cables (18 cm / 7.1 inches)
<b>two hand electrodes:</b>	consisting of V2A steel (length 12 cm / 4.7 inches, diameter 3 cm / 1.2 inches), connecting cable (2 m / 6.6 feet)

<b>Order No. MEDISEND®super C:</b>	<b>204</b>
with interface for PC:	
<b>Order No. MEDISEND®super:</b>	<b>201</b>
without interface for PC:	
<b>Order No. MEDICUP:</b>	<b>501</b>
<b>Order No. hand electrodes:</b>	<b>503</b>

To see the current USD price and place your order please check our website and online shop:

[www.magnetotherapy.de](http://www.magnetotherapy.de)

Please order...

by telephone: +49 (0) 7934 / 99 34 89 - 0  
or in our online shop  
[www.magnetotherapy.de](http://www.magnetotherapy.de)

AMS GmbH

Advanced Medical Systems

Hauptstr. 26 • D-97990 Weikersheim • GERMANY

Tel.: +49 (0)79 34 / 99 34 89-0 • [info@ams-ag.de](mailto:info@ams-ag.de) • [www.magnetotherapy.de](http://www.magnetotherapy.de)

Thank you

**Good to know: If you buy a large and a small device together, you will receive a 10% discount on the small device.**

Learn more about the **AMScomsystem**, **CEPES-Laser®Vario** and the **METRONOM C** in the particular product brochures or our complete catalog. You find a complete listing of all digitized BIOWAVES in our **BIOWAVE catalog**. Please email us to ask for the documents or visit our website for download: [info@ams-ag.de](mailto:info@ams-ag.de) / [www.magnetotherapy.de](http://www.magnetotherapy.de)